

# HYDRAULIC MOTOR DRIVE 液驱

## PRODUCT SPECIFICATION 标准配置参数



型号	SS0507	AS0607	AS0607W	AS0608	AS0808	S0812	S1012	S1212	AS1413
安全工作载荷 Platform Capacity	230Kg	230Kg	230Kg	380Kg	230Kg	450Kg	320Kg	320Kg	>10 m 200kg <10m 320kg
延伸平台安全工作载荷 Capacity On Deck Extension	113Kg	120Kg	120Kg	113Kg	113Kg	120Kg	120Kg	120Kg	113Kg
最大工作人数 Platform Occupants	2	2	2	2	2	2	2	2	2
最大工作高度(A+2) Work Height (A+2)	6.3m	7.8m	7.8m	7.9m	10m	10m	12m	14m	15.8m
整机长度(B) Overall Length (B)	1.53m	1.83m	1.83m	2.40m	2.40m	2.49m	2.49m	2.49m	2.79m
整机宽度(C) Overall Width (C)	0.81m	0.76m	0.81m	0.83m	0.83m	1.18m	1.18m	1.18m	1.27m
整机高度(围栏折叠) Overall Height - Rails Down	1.91m	1.82m	1.82m	1.83m	1.95m	1.8m	1.93m	2.05m	2.27m
整机高度(围栏未折叠) Overall Height - Rails Up	2.15m	2.12m	2.12m	2.19m	2.32m	2.38m	2.5m	2.65m	2.78m
平台延伸尺寸 Platform Extension	0.6m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9	0.9m
机器行使速度(收藏/举升) Drive Speed(Lowered / Elevated)	40.5 Km/h	35.0.8Km/h	35.0.8Km/h	35.0.8Km/h	35.0.8Km/h	30.8Km/h	30.8Km/h	30.8Km/h	35.0.8Km/h
上升/下降速度 Lift / Lower Time	25/20sec	16/28sec	16/28sec	30/34sec	31/40sec	35/40sec	58/48sec	65/60sec	80/65sec
最大爬坡能力 Gradeability	25%	25%	25%	25%	25%	25%	25%	25%	25%
工作最大允许角度 Max. Slope	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°
整机重量 Machine Weight	990Kg	1580Kg	1600Kg	1835Kg	2140Kg	2350kg	2625Kg	3175Kg	3500Kg

- ❌ 行业内耐用可靠的叉架;
- ❌ 全新优化的上平台;
- ❌ 行业内可靠性高的充电器;
- ❌ 注重细节, 细节之处显实力;

Most durable and reliable scissor stacks

Reinforced working platform

Advanced charger with voltage protection

Higher driver comfort and security

