

HYDRAULIC MOTOR DRIVE



- Most durable and reliable scissor stacks
- Reinforced working platform
- Advanced charger with voltage protection
- Higher driver comfort and security

PRODUCT SPECIFICATION

Model	AS0607	AS0607W	AS0608	AS0808	AS0812	AS1012	AS1212	AS1413
Platform Capacity	230 kg	230 kg	380 kg	230 kg	450Kg	320 kg	320 kg	>10 m 200kg <10m 320kg
Capacity On Deck Extension	120 kg	120 kg	113 kg	113 kg	113Kg	113 kg	113 kg	113 kg
Platform Occupants	2	2	2	2	2	2	2	2
Work Height(A+2)	7.8 m	7.8 m	7.9 m	10 m	10m	12 m	14 m	15.8 m
Overall Length(B)	1.83 m	1.83 m	2.40 m	2.40 m	2.42m	2.47 m	2.47 m	2.79 m
Overall Width(C)	0.76 m	0.81 m	0.83 m	0.83 m	1.18m	1.18 m	1.18 m	1.27 m
Overall Height - Rails Down	1.82m	1.82m	1.83 m	1.95 m	1.73m	1.86 m	1.99 m	2.27 m
Overall Height - Rails Up	2.12m	2.12m	2.19m	2.32m	2.3m	2.43m	2.56m	2.78m
Platform Extension	0.9 m	0.9 m	0.9 m	0.9 m	0.9m	0.9 m	0.9 m	0.9 m
Drive Speed (Lowered/Elevated)	3.5/0.8 km/h	3.5/0.8 km/h	3.5/0.8km/h	3.5/0.8 km/h	3.5/0.8Km/h	3.5/0.8 km/h	3.1/0.8 km/h	3.5/0.8 km/h
Lift/Lower Time	16/28 sec	16/28 sec	30/34 sec	31/40 sec	35/40sec	62/48 sec	65/60 sec	80/65
Gradeability	25%	25%	30%	25%	25%	25%	25%	25%
Max. Slope	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	2°/3°	1.5°/3°	1.5°/3°
Machine Weight	1,580 kg	1,600 kg	2,000 kg	2,140 kg	2.691Kg	3,000 kg	3,300 kg	3,500 kg

