

ELECTRIC MOTOR DRIVE 电驱

PRODUCT SPECIFICATION 标准配置参数



🔧 整机合理匹配, 整机续航能力高

🔧 优化了电控, 克服了长下坡溜车;

🔧 合理的转向机构, 降低转弯中轮胎磨损;

🔧 蓄电池驱动, 绿色环保。

Optimization and match of hydraulic system delivers longer lasting performance

Optimized electronic control system for better brake ability on a long downhill

Improved steering mechanism reduces tire wear during turning

Battery powered with zero emission and environmental-friendly

型号	SS0407E	SS0507E	SS0607E	AS0607E	AS0607WE	AS0608E	AS0808E	AS0812E	AS1012E	AS1212E
安全工作载荷 Platform Capacity	240kg	230kg	230kg	230kg	230kg	380kg	230kg	450kg	320kg	320kg
延伸平台安全工作载荷 Capacity On Deck Extension	113kg	113kg	113kg	120kg	120kg	113kg	113kg	113kg	113kg	113kg
最大工作人数 Platform Occupants	2	2	2	2	2	2	2	2	2	2
最大工作高度(A+2) Work Height	5.6m	6.3m	7.5m	7.8m	7.8m	7.9m	10m	10m	12m	14m
整机长度(B) Overall Length (B)	1.53m	1.53m	1.53m	1.86m	1.86m	2.40m	2.4m	2.42m	2.47m	2.47m
整机宽度(C) Overall Width (C)	0.76m	0.81m	0.81m	0.76m	0.81m	0.83m	0.83m	1.18m	1.18m	1.18m
整机高度(围栏折叠) Overall Height - Rails Down	1.82m	1.9m	2m	1.84m	1.84m	1.83m	1.95m	1.73m	1.86m	1.99m
整机高度(围栏未折叠) Overall Height - Rails Up	2.06m	2.15m	2.275m	2.14m	2.14m	2.19m	2.32m	2.30m	2.43m	2.56m
平台延伸尺寸 Platform Extension	0.6m	0.6m	0.6m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m
机器行使速度(收藏/举升) Drive Speed(Lowered/Elevated)	4/0.5km/h	4/0.5km/h	3.8/0.5km/h	4/0.8km/h	4/0.8km/h	3.5/0.8km/h	3.5/0.8km/h	4/0.8km/h	4/0.8km/h	4/0.8km/h
上升/下降速度 Lift / Lower Time	25/18sec	25/20sec	32/27sec	16/28sec	16/28sec	30/34sec	31/40sec	35/40sec	58/48sec	58/60sec
最大爬坡能力 Gradeability	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%
工作最大允许角度 Max. Slope	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	1.5°/3°	2°/3°	1.5°/3°
整机重量 Machine Weight	880kg	970kg	1300kg	1610kg	1620kg	2000kg	2140kg	2715kg	3000kg	3300kg

